

BlueEye™ Ex-D



Gas quality analyzer
Reliable, no moving parts
Fast response time
Low CAPEX, no OPEX

BROCHURE v24.05.23



About the BlueEye™ Ex-D


The BlueEye™ Ex-D is a low CAPEX gas analyzer, designed for the continuous measurement of combustible gases. Every second the device accurately reports the combustion properties (**H_s**, **H_i**, **W_i**, **W_L**, **p**, **Z**, **s-AFR**, **MN**, **CO₂**, **H₂ mol%**) of gas compositions.

Gas enters at flow rate (50 ml/min) the BlueEye™ Ex-D through 3/4 NPT connectors. Measurement output is interfaced through 4-20 mA current loop and Modbus RTU.

The BlueEye™ Ex-D uses Bright Sensors' patented MEMS gas viscometer technology combined with other MEMS sensors. The analyzer is specifically developed for biomethane injection, hydrogen blending, combustion control, gas grid monitoring and other stationary process applications.

The sensor units come in 4 different versions for specific accuracy and gas composition ranges:

- BlueEye™ **Extended**: Viscosity + TCD sensor
- BlueEye™ **Renewable**: Viscosity + TCD + **CO₂** sensor
- BlueEye™ **Hydrogen**: Viscosity + TCD + **H₂** hardware
- BlueEye™ **Ultragreen**: Viscosity + TCD + **CO₂** + **H₂** hardware



Main Features

Measurement output:

- Wobbe Index (W_i & W_L)
- Calorific content (H_s & H_i)
- **H₂** and **CO₂** mol% (optional)
- Density, relative density & compressibility
- stoichiometric Air Fuel Ratio
- Methane Number

Accuracy:

- Wide composition range, typically <1%
- Other gas compositions on request

Maintenance free & reliable

- No moving parts
- No chemical reactions

Fast & continuous measurement

- 7 second Viscosity
- 1 second Thermal Conductivity and CO₂

Other features:

- Explosion proof certified enclosure
- Built-in flow reducer
- Interface: 4-20mA, Modbus RTU
- Input Power: 24VDC
- Plug-and-play installation & operation
- Easy replacement of sensor unit
- CE, ATEX & IECEx certified
- OILM R140 Class B in progress
- Cabinet solutions available

BlueEye™ Ex-D Specifications

Reported values	Units	Reference conditions	Applied correlation standards
Gross Calorific Value (H_s)	MJ/m ³ , kWh/m ³	0/0°C, 15/0°C, 15/15°C,	NIST AGA-8
Net Calorific Value (H_i)	BTU/scf,	20/20°C, 25/20°C, 25/0°C at	ISO 6976:2016
Gross Wobbe Index (W_s)	Therm/scf	101325 Pa and 60°F	GPA 2172:2009
Net Wobbe Index (W_i)		at 14.65, 14.696, 14.73 and	
Density ρ	kg/m ³ , lbm/scf	15.025 psi absolute	
Air Fuel Ratio λ	-	Volume, 20.946% O ₂	Simplified method
Methane Number	-	-	ISO23306 PKI Methane Number
CO ₂ & H ₂ concentration ^{1 2}	mol%	-	Proprietary methods

Accuracy	≤ 1% of reading
Repeatability	≤ 0.2% of reading ³
Dynamics	One measurement every 1s, reaction time T90 < 60s

Gas Composition Range					
CH ₄	70-100 mol%	Higher Alkanes	0-1 mol%	O ₂	≤ 3 mol%
C ₂ H ₆	0-20 mol%	N ₂	0-15 mol%	H ₂ O (Gaseous)	≤ 0.1 mol%
C ₃ H ₈	0-5 mol%	CO ₂	0-3 mol% (20/100 mol%) ¹	Dust, Liquids	Without
C ₄ H ₁₀	0-3 mol%	H ₂	≤ 0.5 mol% (30 mol%) ²	H ₂ S	≤ 0.01 mol%
H _s addressable range	27.52 to 50.40 MJ/m ³ (15°C/15°C)				
Environment temperature	0 to 50°C, 32 to 122°F				
Operating gas pressures	960 to 1100 mbar absolute , 13.9 to 16 psi absolute				
Flow rate	50 ml/min (+/- 10%), 0.00177 scf/min (+/- 10%) ⁴				


¹ only for BlueEye™ Ex-D **Renewable** & **Ultragreen**

² only for BlueEye™ Ex-D **Hydrogen** & **Ultragreen**

³ unfiltered 1 second cycle measurement

⁴ flow rate range customizable on request

Electrical and Mechanical Specifications

Interfaces	Modbus RTU (RS485), analog output (4-20mA current loop)
Supply Voltage	24V, < 2W
Dimensions and Weight	140mm x 135mm x 125mm and 2.6kg, 5.51in x 5.32in x 4.92in and 5.7 lbs
Gas Connections	2 x 1/4" NPT (Female)
Certifications	CE, IECEx, ATEX  II 2 G Ex db IIC T6 Gb UL/CSA. OIML R140 Class B in progress

Environment Conditions

Operating Temperature	-20°C to 70°C, -4°F to 158°F
Storage Temperature	-40°C to 70°C, -40°F to 158°F
Environment Humidity	0-95 % Relative Humidity, non-condensing
Burst Pressure	< 250 mbar gauge , < 3.6 psi gauge

